



PHICAL CO., LTD.
en zhe



• 冗余直流电

及高可靠性要求

- 高功率因数(APFC)软开关技术设计,体积小重量轻
- 具备良好的电磁兼容性






输出电流@额定				
MANGO80H-12	12V	6.66A	±5%	10.0A
MANGO80H-15	15V	5.33A	±5%	8.0A
MANGO80H-19	19V	4.21A	±5%	6.3A
MANGO80H-24	24V	3.33A	±5%	5.0A

输出电流				
MDP120-19y	19V	6.3A	190mV	±5%
MDP120-24y	24V	5.0A	240mV	±5%

	输出电流	峰值电流@10S	峰值电流@40mS	总
12V		25.00A	35.0A	±5%
15V		22.00A	30.0A	±5%
19V		18.50A	25.0A	±5%
24V	00A	15.00A	20.0A	±5%
28V	8.57A	12.85A	17.5A	±5%
32V	7.50A	11.25A	15.0A	±5%
36V	6.66A	10.00A	13.3A	±5%
48V	5.00A	7.50A	10.0A	±5%

开放式电源

- 通用AC输入且部分带主动式PFC Class I or Class II 结构
- 高效率 Level V or Level VI
- 符合医疗 00001 1 类认证(符合CEC 2000 / EN 2 / IEC 2004 标准)
- 符合EN55011 / FCC Part 15 Class B Emissions
- 3年质保



	5.6A	8
	5.6A	4
	5.6A	
	5.41A	
	4.33A	
	3.61A	
	2.71A	

总调整率(含设定点)

产品型号	输出电压	出电流	纹波及噪声(最大值)
------	------	-----	------------

MP300S系列

尺寸: 5x3x1.5"

产品型号	输出电压	输出电流	纹波及噪声(最大值)	总调整率(含设定点)
MP300S-12	12V	25.0A	200mV	±2%
MP300S-15	15V	20.0A	200mV	±2%
MP300S-19	19V	15.8A	280mV	±2%
MP300S-24	24V	12.5A	250mV	±2%
MP300S-28	28V	10.8A	280mV	±2%
MP300S-36	36V	8.33A	480mV	±2%
MP300S-48	48V	6.25A	480mV	±2%

MP400系列

尺寸: 7x3.94x1.58"



MP400-12		30.0A		120mV	
MP400-15				150mV	
				180mV	
				240mV	
				280mV	
				360mV	
				480mV	

