

深圳麦格米特电气股份有限公司
SHENZHEN MEGMEET ELECTRICAL CO., LTD.

地址：

ict, Shenzhen, 518057, China

版本：202509
本手册技术参数仅供参考
Megmeet reserve

米特所有



• 冗余直流电

外置适配器

Extern

	8.33A
	6.66A
	5.20A
	4.16A

	10.0A
	8.0A
	7.9A
	7.5A

	10.0A
--	-------

无线

符合CEC 2006 / EN 2 / EN 12004 标准,

符合EN55011 / FCC Part 15 Class B Emissions

- 3年质保



	5.6A	80mV
	5.6A	80mV
	5.6A	80mV
	5.41A	
	4.33A	
	3.61A	
	2.71A	

MP300S系列

尺寸: 5x3x1.5"


产品型号	输出电压	输出电流	纹波及噪声(最大值)	总调整率(含设定点)
MP300S-12	12V	25.0A	200mV	±2%
MP300S-15	15V	20.0A	200mV	±2%
MP300S-19	19V	15.8A	280mV	±2%
MP300S-24	24V	12.5A	280mV	±2%
MP300S-28	28V	10.8A	280mV	±2%
MP300S-36	36V	8.33A	480mV	±2%
MP300S-48	48V	6.25A	480mV	±2%

MP400系列

尺寸: 7x3.94x1.58"



MP400-12		30.0A	120mV	
MP400-15				
		22.2A	180mV	
		16.67A	240mV	
		14.2A	280mV	
		11.1A	360mV	
		8.33A	480mV	



输出

9A	150m
6A	
7A	
1.5A	
1.5A	
0.1A	
12A	

